

FUEGO INDICATOR - MODEL: EIR2NF

In-ground Luminaires




PROJECT:

TYPE:

Product Image



Line Drawing



Product Description

The overall stainless steel material of the FUEGO Indicator is precision cast, with a circular appearance and an IP68 protection level, suitable for underwater environments. It has an IK08 impact resistance level and can withstand pressure of 500kg. The design of stainless steel shrapnel can support wall or tube lamp installation.

Product Features

- Body Material: Overall stainless steel material
- Optical System: Lens
- Finish: /
- Adjustable Angle: /
- Accessories: /
- Certification: CQC
- IP Rating: IP68
- Insulation Level: Class III
- Operating Temperature: -20°C~50°C

Product Specifications

- LED Type: High Power
- Power: 2W(Max)
- Source Lm: 3000K 260lm ;4000K 260lm;Amber; Blue
- LED Lifetime: >50000h-L70 /B10-Ta25°C(LM-80/TM-21)
- CCT/CRI: 3000K,Ra85 / 4000K ,Ra85
- SDCM: 3 SDCM
- Input: 9-15V/AC
- Dimming: ON-OFF
- Net Weight: 0.3Kg without packing

Order Model

Model	comment	Power (W)	LEDs (quantity)	Max Lumens (Lm)	Control Systems	Beam	CCT	Finish
EIR2N	F Frame	02 2(Max)	1	80	ET ON-OFF 9-15V/AC Power Supply	5 50°	30 3000K 40 4000K A Amber B Blue	SS Stainless Steel

Example:EIR2NF-02ET-540SS

WAC Lighting

www.waclighting.com (US)
www.waclighting.com.cn (China)

Headquarters

44 Harbor Park Drive • Port Washington, NY
Phone (516) 515.5000 • Fax (516) 515.5050

WAC Lighting(Shanghai)

14,Lane 299, Bi Sheng Road,Shanghai 201204
Phone (86.21) 3393.3558 • Fax (86.21) 3362.1598

FUEGO INDICATOR - MODEL: EIR2NF

In-ground Luminaires


WAC

PROJECT:

TYPE:

Accessory

LIGHT distribution@3000K IUMINAIRE DATA



MODEL:	EIR2NF-02ET-530SS
BEAMANGLE:	50°
POWER:	3W (Max)
LUMENS:	80 lm
CBCP:	/
EFFICACY:	23 lm /W