

FUEGO INDICATOR - MODEL: EIS4SF

In - ground Luminaires

WAC


PROJECT:

TYPE:

Product Image



Line Drawing



Product Description

FUEGO Indicator overall stainless steel, seiko casting, square appearance, IP68 protection grade, suitable for underwater environment, IK08 anti-impact grade, can resist pressure 500kg. Embedded cylinder installation.

Product Features

- Body Material: Overall stainless steel
- Optical System: Lens optical system
- Finish: /
- Adjustable Angle: /
- Accessories: /
- Certification: CQC
- IP Rating: IP68
- Insulation Level: Class III
- Operating Temperature: -20°C~50°C

Product Specifications

- Lamp Power: 4W(Max)
- LED Type: HP LED
- Source Lm: 3000K 500LM; 4000K 500LM; Amber; Blue;
- LED Lifetime: >50000h-L70 /B10-Ta25°C(LM-80/TM-21)
- CCT/CRI: 3000K, Ra85/4000K, Ra85
- SDCM: 3 SDCM
- Input: 9-15V AC
- Dimming: ON-OFF
- Net Weight: 0.7Kg without packing

Order Model

Model	Comment	Power(W)	LED(quantity)	Max Lumens	Control	Systems	Beam	CCT,	Finish
EIS4S	F Frame	04 4(Max)	1	170	ET	ON-OFF 9-15V/AC Power Supply	2 25°	30 3000K 40 4000K A Amber B Blue	SS Stainless Steel

Example: EIS4SF-04ET-240SS

FUEGO INDICATOR - MODEL: EIS4SF


In - ground Luminaires

WAC


PROJECT:

TYPE:

Accessories

Item	Pic	Small Version
Single Directional (Round Frame)		EIS2SF-SDSF-SS

LIGHT DISTRIBUTION@3000K LUMINAIRE DATA



MODEL:	EIS4SF-04ET-230SS
BEAM ANGLE:	25°
POWER:	6W (Max)
LUMENS:	170 lm
CBCP:	/
EFFICACY:	28 lm /W