

PLANA PRO - MODEL: SDL42

Ceiling Mount Luminaires

WAC


PROJECT:

TYPE:

Product Image



Line Drawing



Product Description

PLANA PRO surface mounted tube light, exquisite and simple overall, with precise light distribution, using SUBROSA® Hidden light technology, while also having the ultimate anti glare effect. Mainly suitable for hotels, commercial public spaces, and exhibition venues.

Product Features

- Body Material: Aluminum alloy extruded lamp body
- Optical System: Lens+ SUBROSA® Hidden light system
- Finish: Static electricity powder coating
- Adjustable Angle: /
- Accessories: /
- Certification: CCC
- IP Rating: IP20(Light source cavity IP44)
- Insulation Level: Class I
- Operating Temperature: -20°C~40°C

Product Specifications

- Shielding Angle: 35°
- LED Type: COB
- Source Lm: 1800lm/18W 3000K; 2500lm/25W 3000K
- LED Lifetime: >50000h-L70 /B10-Ta25°C(LM-80/TM-21)
- CCT/CRI: 2700K/3000K/3500K/4000K/5000K, Ra90
- SDCM: 3 SDCM
- Input: 220V~240V AC / 50Hz
- Dimming: On-off / 0-10V (Must conduct compatibility testing with the project site system in advance)
- Net Weight: 1 Kg without packing

Order Model

Model	Size	Trim	LED	Driver	Beam	CCT	Reflector	Finish
SDL	4	2	LM18	E ON-OFF	2 20°	27 2700K	B Black	WT White
Surface	4"	Round	COB 18W	D 0-10V	4 40°	30 3000K	S Specular	BK Black
Mount		Trimless	LM25	Dimming	6 60°	35 3500K		
Downlight			COB 25W			40 4000K		
						50 5000K		

Example: SDL42-LM18-D230SWT

Accessories

/

PLANA PRO - MODEL: SDL42


Ceiling Mount Luminaires



PROJECT:


TYPE:

LIGHT DISTRIBUTION@3000K LUMINAIRE DATA




MODEL:	SDL42-LM18-D230SWT
BEAM ANGLE:	20°
POWER:	21 W
LUMENS:	1681 lm
CBCP:	8154 cd
EFFICACY:	80 lm/W

MODEL:	SDL42-LM25-D230SWT
BEAM ANGLE:	20°
POWER:	29 W
LUMENS:	2123 lm
CBCP:	10326 cd
EFFICACY:	73 lm/W



MODEL:	SDL42-LM18-D430SWT
BEAM ANGLE:	40°
POWER:	21 W
LUMENS:	1404 lm
CBCP:	2604 cd
EFFICACY:	67 lm/W

MODEL:	SDL42-LM25-D430SWT
BEAM ANGLE:	40°
POWER:	29W
LUMENS:	1827 lm
CBCP:	3422 cd
EFFICACY:	63 lm/W



MODEL:	SDL42-LM18-D630SWT
BEAM ANGLE:	60°
POWER:	21 W
LUMENS:	1760 lm
CBCP:	1984 cd
EFFICACY:	84 lm/W

MODEL:	SDL42-LM25-D630SWT
BEAM ANGLE:	60°
POWER:	29W
LUMENS:	2274 lm
CBCP:	2593 cd
EFFICACY:	78 lm/W