

PLANA PRO - MODEL: SDL52

Ceiling Mount Luminaries

WAC


PROJECT :

TYPE :

Product Image



Line Drawing



Product Description

PLANA PRO surface mounted tube light, exquisite and simple overall, with precise light distribution, using SUBROSA ® Hidden light technology, while also having the ultimate anti glare effect. Mainly suitable for hotels, commercial public spaces, and exhibition venues.

Product Features

- Body Material: Aluminum alloy extruded lamp body
- Optical System: Lens+ SUBROSA ® Hidden light technology
- Finish: Static electricity powder coating
- Adjustable Angle: /
- Accessories: /
- Certification: CCC
- IP Rating: IP20
- Insulation Level: Class I
- Operating Temperature: -20°C~40°C

Product Specifications

- Shielding angle: 35 °
- LED Type: COB
- Source Lm: 3830lm/32W 3000K; 4500lm/40W 3000K
- LED Lifetime: >50000h-L70 /B10-Ta25°C(LM-80/TM-21)
- CCT/CRI: 2700K/3000K/3500K/4000K/5000K Ra90
- SDCM: 3 SDCM
- Input: 220~240V/AC , 50Hz
- Dimming: ON-OFF/0-10V
(Conduct compatibility testing in advance)
- Net Weight: 1.5Kg without packing

Order Model

Model	Size	Trim	LED	Driver	Beam	CCT	Reflector	Finish
SDL Surface Mount Downlight	5 5 "	2 Round Trimless	LM 32	E ON-OFF D 0-10V Dimming	1 15 ° 2 24 ° 3 36 °	27 2700K	B Black S Specular	WT White BK Black
			COB 32W			30 3000K		
			LM 40			35 3500K		
			COB 40W			40 4000K		
						50 5000K		

Example : SDL52-LM40-D230SWT

Accessories

/

PLANA PRO - MODEL: SDL52


Ceiling Mount Luminaries

WAC


PROJECT :

TYPE :


LIGHT DISTRIBUTION@3000K LUMINAIRE DATA



MODEL :	SDL52-LM32-D130SWT	SDL52-LM40-D130SWT
BEAM ANGLE :	15 °	15 °
POWER :	35W	43W
LUMENS :	3017 lm	3688 lm
CBCP :	21993 cd	26804 cd
EFFICACY :	86 lm /W	86 lm /W



MODEL :	SDL52-LM32-D230SWT	SDL52-LM40-D230SWT
BEAM ANGLE :	24 °	24 °
POWER :	35W	43W
LUMENS :	2885 lm	3526 lm
CBCP :	12543 cd	15330 cd
EFFICACY :	82 lm /W	82 lm /W



MODEL :	SDL52-LM32-D330SWT	SDL52-LM40-D330SWT
BEAM ANGLE :	36 °	36 °
POWER :	35W	43W
LUMENS :	2950 lm	3605 lm
CBCP :	6924 cd	8463 cd
EFFICACY :	84 lm /W	84 lm /W